

Flockomat
Absolut staubfrei.

NEW THE FLOCKOMAT

THE SOLUTION TO YOUR DUST PROBLEM!

Effective & dust-free production – thanks to the new Flockomat, the first flaking machine that does not generate any dust at all

FLOCKOMAT 100

- continuously variable roller adjustment
- 2 x 1.5 kW motor ready to use and with overload protection
- Control display
- Automatic switch-off via capacity detector
- Absolutely dust-free environment thanks to aspiration
- Stainless steel machine body
- Rollers made of hardened steel
- Volumetric dosing with steady material feed
- dust suction system with self-cleaning filters
- Tank connection with sliding sleeve to guarantee dust-free infeed
- Motorised drive on each roller at 1:1 ratio
- Two profiled rollers for uniform flakes
- Self-cleaning rollers thanks to adjustable stripper plates made of stainless steel

FEED

- The electronically operating volumetric feeding system allows the flockomat to flake cereals continuously
- motorised drive on each roller at 1:1 ratio
- Flange mounted hopper with magnet

AVAILABLE VERSIONS

- The Flockomat can be integrated in fully automated plants
- The Flockomat and the Shrotomat jointly mounted on one base plate with dust collection system
- The Flockomat or the Shrotomat individually mounted on a base plate with dust collection system.



Type	roller width	Dimensions D x W x H (m)	Power input	Connection	Weight
Flockomat 100	100 mm	1.2 x 0.8 x 1.67	5 kW	230/400 V 16 A	300 Kg



TREFFLER MASCHINENBAU GMBH & CO. KG

Telefon: +49 (0) 82 53-99 58-0
Telefax: +49 (0) 82 53-99 58-70

Reichersteiner Straße 24
86554 Pöttmes-Echsheim

info@treffler.net
www.treffler.net