

THE SCHROTOMAT

THE SOLUTION TO YOUR DUST PROBLEM!

Effective & dust-free production ... thanks to the new Schrotomat, the first mill to produce meal and semolina without any dust at all

SCHROTOMAT

- o continuously variable roller adjustment from 0 mm to 5 mm
- o 2 x 1.5 KW motor ready to use and with overload protection
- Control display

In combination

with the Flockomat

- Automatic switch-off via capacity detector
- Absolutely dust-free environment thanks to aspiration
- Stainless steel machine body
- o Volumetric dosing with steady material feed
- o dust suction system with self-cleaning filters
- Tank connection with sliding sleeve to guarantee dust-free in-feed
- Motorised drive on each roller at 1:2 ratio
- Profiled steel rollers for steady in-feed
- Stripper plates made of stainless steel create a self-cleaning mechanism for the rollers

THE FEED MECHANISM

- The electronically operated feeding device assures steady in-feed of the material to the Schrotomat.
 - No need for manual ajustment.
 - Flange-mounted aluminium hopper with magnetic separator

AVAILABLE VERSIONS

- Possibility to build the Schrotomat into a fully-automated system
- Flockomat and Schrotomat can be provided both built on one frame with dust aspiration system.
 - Alternatively Flockomot or Schrotomat individually on one base plate with dust.

Туре	Rollers width	Measures l x w x h (m)	Power input	Connection needed	Weight
Schrotomat	100 mm	1.2 × 0.8 × 1.67	5 kW	230/400 V 16 A	300 Kg



TREFFLER MASCHINENBAU GMBH & CO. KG

phone: +49 (0) 82 53-99 58-0

fax: +49 (0) 82 53-99 58-70

Reichersteiner Straße 24 86554 Pöttmes-Echsheim info@treffler.net www.treffler.net